NSN 5905-00-764-7731

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-764-7731 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 4.925 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Actuator Type:** Dual concentric **Nonturn Device Radius:** 0.438 inches **Fragility Factor:** Moderately rugged **Undercut Length:** 2.463 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.0 kilohms all sections **Power Dissipation Rating Per Section In Watts:** 0.5 free air 3rd section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 all sections **Standard Taper Curve Per Section:**

A all sections **Terminal Type And Quantity:** 9 tab, solder lug Shelf Life:

N/a

Unit Of Measure:

NSN 5905-00-764-7731

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A002a0