

View Online at <https://aerobasegroup.com/nsn/5905-00-765-5552>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

Between 0.850 inches and 0.890 inches

Terminal Length:

0.130 inches

Overall Height:

Between 0.300 inches and 0.320 inches

Overall Width:

Between 0.150 inches and 0.170 inches

Mounting Hole Diameter:

Any acceptable

Shaft Diameter:

Between 0.105 inches and 0.115 inches

Shaft Length:

Between 0.110 inches and 0.130 inches

Body Length:

Between 0.740 inches and 0.760 inches

Body Width:

Between 0.150 inches and 0.170 inches

Body Height:

Between 0.300 inches and 0.320 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

5400.0

Maximum Starting Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.490 inches and 0.510 inches

Lateral Distance Between Mounting Hole Centers:

Any acceptable

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Electrical Resistance Per Section:

50.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

5400.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.290 inches and 0.310 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-400.0 to 400.0 single section

Power Dissipation Rating Per Section In Watts:

0.2 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0