NSN 5905-00-765-9844

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-765-9844

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.906 inches
Body Diameter:
1.690 inches
Shaft Diameter:
0.249 inches
Shaft Length:
0.313 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.390 inches
Overall Diameter:
1.672 inches
Shaft Style:
Round
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
250.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
1.00 inch-ounces
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:
0.531 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, double throw, three positions maintained

NSN 5905-00-765-9844

Precision Wire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
75.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0/+2.0 ohms single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
3750.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
65.0 single section
Switch Current Type And Rating In Amps:
2.000 ac/dc
Terminal Type And Quantity:
5 tab, solder lug and 1 turret
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-765-9844

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0