

View Online at <https://aerobasegroup.com/nsn/5905-00-766-8329>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.141 inches

**Body Diameter:**

1.094 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

1.266 inches

**Overall Diameter:**

1.874 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

100.0 kilohms all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0