

View Online at <https://aerobasegroup.com/nsn/5905-00-766-8345>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 0.923 inches and 0.953 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.343 inches

**Mounting Bushing Length:**

0.188 inches

**Body Length:**

Between 0.870 inches and 0.890 inches

**Undercut Diameter:**

0.125 inches

**Shaft Style:**

Round, stepped

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.437 inches

**Fragility Factor:**

Moderately rugged

**Undercut Length:**

0.172 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unc

**Screw Thread Qty Per Inch (tpi):**

56.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

1.0 kilohms 2nd section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-1.0 to 1.0 all sections

**Standard Taper Curve Per Section:**

C 1st section

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0