

View Online at <https://aerobasegroup.com/nsn/5905-00-766-8345>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 0.923 inches and 0.953 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.343 inches

Mounting Bushing Length:

0.188 inches

Body Length:

Between 0.870 inches and 0.890 inches

Undercut Diameter:

0.125 inches

Shaft Style:

Round, stepped

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.437 inches

Fragility Factor:

Moderately rugged

Undercut Length:

0.172 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unc

Screw Thread Qty Per Inch (tpi):

56.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.0 kilohms 2nd section

Power Dissipation Rating Per Section In Watts:

1.0 free air all sections

Resistance Tolerance Per Section In Percent:

-1.0 to 1.0 all sections

Standard Taper Curve Per Section:

C 1st section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0