NSN 5905-00-767-0645

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-767-0645

Electrical Resistance: 15.000 ohms Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Impurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Incapsulated Iterminal Type: Wire lead Reliability Indicator: Istablished Reliability Failure Rate Level In Percent: I.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+15.0 Inclosure Method: Inclosure Metho
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
In Exemperature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Incapsulated I
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Inclosure Method: Inclosure Method: Incapsulated Incapsul
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Established Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Reliability Failure Rate Level In Percent: 1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
1.000 Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Body Diameter: 0.318 inches Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
D.318 inches Body Length: D.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Body Length: 0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
0.688 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator:
Power Dissipation Rating In Watts: 2.000 free air Style Designator:
2.000 free air Style Designator:
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0