

| NSN 5905-00-767-6778  |
|---|
| Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2                  |
| View Online at https://aerobasegroup.com/nsn/5905-00-767-6778               |
| Section Quantity:   |
| 1   |
| Body Style:   |
| Cylindrical   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 0.188 inches  |
| Body Diameter:  |
| 0.500 inches  |
| Body Length:  |
| 0.562 inches  |
| Actuator Type:  |
| Flush drive with slot-hole  |
| Effective Electrical Rotation In Deg Angular Rotation:                      |
| 295.0   |
| Center To Center Distance Between Terminals:                                |
| 0.562 inches  |
| Fragility Factor:   |
| Moderately delicate   |
| Terminal Location:  |
| Rear end  |
| Mounting Method:  |
| Terminal  |
| Electrical Resistance Per Section:  |
| 2.5 kilohms single section  |
| Rotary Actuator Travel In Angular Deg:                                      |
| 305.0   |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| 0.281 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 0.33 free air single section  |
| Resistance Tolerance Per Section In Percent:                                |
| -10.0 to 10.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 70.0 single section   |

Standard Taper Curve Per Section:

A single section

AeroBase Group

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0