## NSN 5905-00-768-3970

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-768-3970 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.813 inches **Body Length:** 0.438 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **End Application:** Missile, minuteman lgm-30; defense support program **Terminal Location:** Rear end **Mounting Method:** Tab **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 500.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Continuous motion **Criticality Code Justification:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** 

A single section

Special Features:

Weapon system essential

## NSN 5905-00-768-3970

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0