## NSN 5905-00-769-5454

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-769-5454 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.938 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.375 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.813 inches **Shaft Style:** Round, slotted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** 

Switch

**Electrical Resistance Per Section:** 

50.0 kilohms single section

## NSN 5905-00-769-5454

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Power Dissipation Rating Per Section In Watts: |
|--|
| 0.333 free air single section                  |
| Resistance Tolerance Per Section In Percent:   |
| -30.0 to 30.0 single section                   |
| Switch Current Type And Rating In Amps:        |
| 3.000 ac/dc                                    |
| Standard Taper Curve Per Section:              |
| A single section                               |
| Terminal Type And Quantity:                    |
| 5 tab, solder lug                              |
| Shelf Life:                                    |
| N/a  |
| Unit Of Measure:                               |
|  |
| Demilitarization:                              |
| No   |

Fiig: A002a0