## NSN 5905-00-769-5455

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-769-5455 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 10.0 kilohms single section **Power Dissipation Rating Per Section In Watts: Resistance Tolerance Per Section In Percent:** 

0.5 free air single section -30.0/+30.0 single section **Switch Current Type And Rating In Amps:** 3.000 ac/dc **Terminal Type And Quantity:** 3 tab, solder lug

## NSN 5905-00-769-5455

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0