NSN 5905-00-769-8525

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-769-8525

Electrical Resistance: 3.000 kilohms Resistance Tolerance In Percent: 5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Resistance Tolerance In Percent: 5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Resistance Tolerance In Percent: 5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.205 inches Body Length: 10.593 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Wire lead Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Reliability Indicator: Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Not established Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Body Diameter: 0.205 inches Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
D.205 inches Body Length: D.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Body Length: 0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
0.593 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator:
Power Dissipation Rating In Watts: 1.000 free air Style Designator:
1.000 free air Style Designator:
Style Designator:
Axial terminal each end
Test Data Document:
31349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-22684/3 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0