NSN 5905-00-769-8695

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-769-8695

| View Online at https://aerobasegroup.com/nsn/5905-00-769-8 |
|--|
| Section Quantity: |
| 1 |
| Body Style: |
| Rectangular w/mounting holes/slots |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| Between 1.280 inches and 1.344 inches |
| Terminal Length: |
| 11.500 inches |
| Overall Height: |
| Between 0.312 inches and 0.344 inches |
| Overall Width: |
| Between 0.234 inches and 0.266 inches |
| Mounting Hole Diameter: |
| 0.087 inches |
| Shaft Diameter: |
| Between 0.109 inches and 0.141 inches |
| Shaft Length: |
| Between 0.046 inches and 0.078 inches |
| Body Length: |
| Between 1.234 inches and 1.266 inches |
| Body Width: |
| Between 0.234 inches and 0.266 inches |
| Body Height: |
| Between 0.312 inches and 0.344 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 9000.0 |
| Maximum Starting Torque: |
| 5.00 inch-ounces |
| Lateral Distance Between Mounting Hole Centers: |
| Between 0.995 inches and 1.005 inches |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| |

Unthreaded hole

NSN 5905-00-769-8695

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section: |
|---|
| 100.000 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 9000.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 200.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| 50.0 to 50.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 5.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| 5.0 to 5.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 25.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| 4002a0 |
| |
| |