NSN 5905-00-770-5277

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-770-5277

View Online at https://aerobasegroup.com/nsn/5905-0
Section Quantity:
1
Body Style:
Rectangular w/mounting hole/slot
Reliability Indicator:
Not established
Overall Length:
Between 0.675 inches and 0.755 inches
Terminal Length:
Between 0.285 inches and 0.315 inches
Overall Height:
Between 0.360 inches and 0.390 inches
Overall Width:
Between 0.217 inches and 0.269 inches
Mounting Hole Diameter:
0.074 inches
Shaft Diameter:
Between 0.080 inches and 0.100 inches
Shaft Length:
Between 0.030 inches and 0.050 inches
Body Length:
Between 0.360 inches and 0.390 inches
Body Width:
Between 0.187 inches and 0.219 inches
Body Height:
Between 0.360 inches and 0.390 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.090 inches and 0.110 inches
Mounting Facility Quantity:
1
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole

2.000 kilohms single section

Electrical Resistance Per Section:

NSN 5905-00-770-5277

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:	
9000.0	
Center To Center Distance Between Center Terminal And Outside Terminal:	
Between 0.090 inches and 0.110 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
175.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
50.0 to 50.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
5.0 to 5.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
A002a0	