Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-770-5691

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.254 inches and 1.359 inches **Terminal Length:** 6.000 inches **Overall Height:** Between 0.235 inches and 0.300 inches **Overall Width:** Between 0.235 inches and 0.300 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches Shaft Diameter: Between 0.100 inches and 0.140 inches Shaft Length: Between 0.036 inches and 0.077 inches **Body Length:** Between 1.218 inches and 1.282 inches **Body Width:** Between 0.235 inches and 0.300 inches **Body Height:** Between 0.235 inches and 0.300 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 6120.0 and 9720.0 Maximum Starting Torque: 8.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.490 inches and 0.510 inches **Fragility Factor:** Moderately delicate Lateral Distance Between Mounting Hole Centers: Between 0.109 inches and 0.160 inches



Terminal Location: Lower adjacent side single row **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 25.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 6120.0 and 9720.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.290 inches and 0.310 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -600.0 to 600.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section **Test Data Document:** 81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-r-22097/1 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0