NSN 5905-00-771-5956

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-771-5956

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.719 inches
Body Diameter:
0.688 inches
Shaft Diameter:
0.156 inches
Shaft Length:
0.125 inches
Body Length:
0.375 inches
Shaft Style:
Round
Actuator Type:
Double ended shaft
Effective Electrical Rotation In Deg Angular Rotation:
245.0
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Tab
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0 to 70.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 heat sink single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Actuator Travel Control Feature:
Stone

Stops

NSN 5905-00-771-5956

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A002a0