## NSN 5905-00-771-5957

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-771-5957

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
0.156 inches
Shaft Length:
0.125 inches
Body Length:
0.375 inches
Body Width:
0.750 inches
Body Height:
0.875 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Fragility Factor:
Moderately delicate
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Flange
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.3 heat sink single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section

## NSN 5905-00-771-5957

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



A single section  Terminal Type And Quantity: 3 tab, solder lug  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	Standard Taper Curve Per Section
3 tab, solder lug  Shelf Life: N/a Unit Of Measure: Demilitarization:	A single section
Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization:	3 tab, solder lug
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
NO	No

Fiig: A002a0