## NSN 5905-00-774-4119

**Section Quantity:** 

Reliability Indicator:

Not established

Rectangular w/bushing/slot mounted

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-774-4119

Shaft Diameter:
0.093 inches
Shaft Length:
0.312 inches
Mounting Bushing Length:
0.312 inches
Body Length:
0.437 inches
Body Width:
0.282 inches
Body Height:
0.453 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.187 inches
Lateral Distance Between Mounting Hole Centers:
0.375 inches
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section

## NSN 5905-00-774-4119

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Co	oefficient Of I	Resistance Per	Section In	Ppm Per I	Deg Celsius:
----------------	-----------------	----------------	------------	-----------	--------------

-50.0 to 50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Test Data Document:** 

13499-381-1728 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0