NSN 5905-00-774-8120

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-774-8120 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.375 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Nonturn Device Radius:** 0.313 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 1.5 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section **Switch Current Type And Rating In Amps:**

3.000 ac/dc

NSN 5905-00-774-8120

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
L single section
Terminal Type And Quantity:
3 pin and 2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0