NSN 5905-00-774-8229

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-774-8229

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 0.9683 inches and 0.9688 inches
Pilot Length:
0.0620 inches
Overall Length:
2.870 inches
Undercut Diameter:
0.969 inches
Undercut Width:
0.0625 inches
Body Diameter:
1.067 inches
Shaft Diameter:
0.124 inches
Shaft Length:
0.750 inches
Body Length:
2.120 inches
Overall Diameter:
1.436 inches
Mounting Lip Diameter:
Between 1.0570 inches and 1.0670 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
350.0
Maximum Starting Torque:
1.00 inch-ounces
Maximum Running Torque:
1.00 inch-ounces

NSN 5905-00-774-8229

Maximum Stop Torque:

Precision Wire Wound Variable Resistor - Page 2 of 3



48.00 inch-ounces
Shaft End Play:
0.00300 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.1
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
40.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
354.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.1 free air single section
Function Conformity Per Section:
Single section terminal base linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch and spring
Clutch and spring Function Characteristic Per Section:

100.0 single section

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

NSN 5905-00-774-8229

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0