

View Online at https://aerobasegroup.com/nsn/5905-00-774-8229

## Section Quantity:

1

# Body Style:

Cylindrical servo mounted

## **Reliability Indicator:**

Not established

### **Pilot Diameter:**

Between 0.9683 inches and 0.9688 inches

#### **Pilot Length:**

0.0620 inches

#### **Overall Length:**

2.870 inches

#### **Undercut Diameter:**

0.969 inches

#### **Undercut Width:**

#### 0.0625 inches

**Body Diameter:** 

#### 1.067 inches

Shaft Diameter:

#### 0.124 inches

Shaft Length:

#### 0.750 inches

## Body Length:

2.120 inches

#### **Overall Diameter:**

1.436 inches

#### Mounting Lip Diameter:

Between 1.0570 inches and 1.0670 inches

#### Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Ball

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

350.0

## Maximum Starting Torque:

1.00 inch-ounces

# Maximum Running Torque:

1.00 inch-ounces



#### Maximum Stop Torque:

48.00 inch-ounces

#### Shaft End Play:

0.00300 inches

#### Shaft Runout:

0.001 inches

## Lateral Runout:

0.002 inches

#### Pilot Diameter Runout:

0.00100 inches

#### Shaft Radial Play:

0.001 inches

#### Mechanical Backlash In Deg Angular Rotation:

0.1

#### Terminal Location:

Radially positioned over more than half the circumference

#### Mounting Method:

Clamp ring

#### **Features Provided:**

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

40.000 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

354.0

#### **Function Conformity Tolerance Per Section:**

-0.25/+0.25 single section

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.1 free air single section

#### **Function Conformity Per Section:**

Single section terminal base linearity

#### **Fixed Tap Quantity Per Section:**

1 single section

#### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

#### **Actuator Travel Control Feature:**

Clutch and spring

#### **Function Characteristic Per Section:**

Single section linear

#### Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

100.0 single section



Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0