## NSN 5905-00-775-0625

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-775-0625

Electrical Resistance: 5.200 kilohms Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Availaterminal each end Established Body Diameters: 0.250 free air Style Designator: Availaterminal each end Established Body Diameters: 0.250 free air
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Avail terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.098 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+150.0 Inclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator: Not established Body Diameter:  10.098 inches Body Length:  10.281 inches Power Dissipation Rating In Watts:  10.250 free air Style Designator:  Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.098 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.098 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.098 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.098 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Wire lead  Reliability Indicator: Not established  Body Diameter: 0.098 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator: Axial terminal each end
Reliability Indicator: Not established Body Diameter: 0.098 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminal each end
Not established  Body Diameter:  0.098 inches  Body Length: 0.281 inches  Power Dissipation Rating In Watts: 0.250 free air  Style Designator:  Axial terminal each end
Body Diameter:  0.098 inches  Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end
20.098 inches  Body Length: 20.281 inches  Power Dissipation Rating In Watts: 20.250 free air  Style Designator:  Axial terminal each end
Body Length:  0.281 inches  Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end
D.281 inches  Power Dissipation Rating In Watts: D.250 free air  Style Designator:  Axial terminal each end
Power Dissipation Rating In Watts:  0.250 free air  Style Designator:  Axial terminal each end
0.250 free air  Style Designator:  Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Took Data Dagumanti
Test Data Document:
31349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-22684/1 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A001a0