Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-776-4621

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.300 inches and 1.340 inches **Terminal Length:** Between 0.469 inches and 0.531 inches **Overall Height:** Between 0.769 inches and 0.861 inches **Overall Width:** Between 0.180 inches and 0.200 inches **Mounting Hole Diameter:** 0.093 inches Shaft Diameter: Between 0.100 inches and 0.130 inches Shaft Length: Between 0.060 inches and 0.080 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.300 inches and 0.330 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 8.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.890 inches and 0.910 inches **Fragility Factor:** Moderately delicate Lateral Distance Between Mounting Hole Centers: Between 0.890 inches and 0.910 inches **Terminal Location:** Lower adjacent side single row **Mounting Method:**

Terminal

NSN 5905-00-776-4621

3 pin

N/a

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided: Nonmetallic shaft **Electrical Resistance Per Section:** 5.0 kilohms single section Center To Center Distance Between Center Terminal And Outside Terminal: 0.300 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.8 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Test Data Document:** 81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity: Specification Data:** 81349-mil-r-22097/2 government specification Shelf Life: Unit Of Measure: **Demilitarization:**