Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-776-5516

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Terminal Length:

Between 0.469 inches and 0.624 inches

#### **Overall Height:**

Between 0.235 inches and 0.300 inches

## **Overall Width:**

Between 0.235 inches and 0.300 inches

#### Mounting Hole Diameter:

Between 0.088 inches and 0.098 inches

#### Shaft Diameter:

Between 0.100 inches and 0.140 inches

### Shaft Length:

Between 0.036 inches and 0.077 inches

#### Body Length:

Between 1.218 inches and 1.282 inches

#### Body Width:

Between 0.235 inches and 0.300 inches

#### **Body Height:**

0.275 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

## Maximum Starting Torque:

8.00 inch-ounces

## Center To Center Distance Between Terminals:

Between 0.490 inches and 0.510 inches

## Lateral Distance Between Mounting Hole Centers:

Between 0.109 inches and 0.160 inches

## Mounting Facility Quantity:

2

## **Terminal Location:**

Lower adjacent side two rows

## Mounting Method:

Unthreaded hole



Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 6120.0 and 9720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 7.0 -55 degrees celsius single section and +0.0 to 3.5 -25 degrees celsius single section and -2.5 to 2.5 85 degrees celsius single
section and -6.0 to 6.0 125 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0