NSN 5905-00-777-8314

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-777-8314 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.256 inches and 1.340 inches **Terminal Length:** 10.000 inches **Overall Height:** Between 0.297 inches and 0.328 inches **Overall Width:** Between 0.180 inches and 0.290 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** Between 0.105 inches and 0.141 inches **Shaft Length:** Between 0.060 inches and 0.080 inches **Body Length:** Between 1.225 inches and 1.260 inches **Body Width:** Between 0.180 inches and 0.290 inches **Body Height:** Between 0.297 inches and 0.328 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:**

Rear end

Mounting Method: Unthreaded hole

NSN 5905-00-777-8314

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Reference Number Differentiating Characteristics:
Quality controlled for polaris
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Filig:
A002a0