NSN 5905-00-778-2355

Section Quantity:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-778-2355

NSN 5905-00-778-2355

Precision Wire Wound Variable Resistor - Page 2 of 2



| Terminal Location: |
|---------------------------------------------------------------------|
| Rear end |
| Mounting Method: |
| Unthreaded hole |
| Electrical Resistance Per Section: |
| 500.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Power Dissipation Rating Per Section In Watts: |
| 0.3 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -20.0/+20.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 25.0 single section |
| Terminal Type And Quantity: |
| 2 bracket |
| Reference Number Differentiating Characteristics: |
| As modified by quality controlled for polaris |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |
| |