## NSN 5905-00-778-5415

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-778-5415

-20.0/+20.0 Electrical Resistance: 290.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Electrical Resistance: 290.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
290.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-20.0/+20.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	290.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+145.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 0.500 inches  Body Diameter: 0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.250 free air  Special Features: Terminals spaced 0.150 in. C to c  Style Designator: Axial terminals one end  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-55.0/+145.0
Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 0.500 inches  Body Diameter: 0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.250 free air  Special Features: Terminals spaced 0.150 in. C to c  Style Designator: Axial terminals one end  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length: 0.500 inches  Body Diameter: 0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.250 free air  Special Features:  Terminals spaced 0.150 in. C to c  Style Designator:  Axial terminals one end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Terminal Length:  0.500 inches  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features:  Terminals spaced 0.150 in. C to c  Style Designator:  Axial terminals one end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Wire lead
Terminal Length:  0.500 inches  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features:  Terminals spaced 0.150 in. C to c  Style Designator:  Axial terminals one end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Reliability Indicator:
0.500 inches  Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features: Terminals spaced 0.150 in. C to c  Style Designator:  Axial terminals one end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Not established
Body Diameter:  0.250 inches  Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features:  Terminals spaced 0.150 in. C to c  Style Designator:  Axial terminals one end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Terminal Length:
0.250 inches  Body Length: 0.312 inches  Power Dissipation Rating In Watts: 0.250 free air  Special Features: Terminals spaced 0.150 in. C to c  Style Designator: Axial terminals one end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.500 inches
Body Length:  0.312 inches  Power Dissipation Rating In Watts:  0.250 free air  Special Features:  Terminals spaced 0.150 in. C to c  Style Designator:  Axial terminals one end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Diameter:
0.312 inches  Power Dissipation Rating In Watts: 0.250 free air  Special Features: Terminals spaced 0.150 in. C to c  Style Designator: Axial terminals one end  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Power Dissipation Rating In Watts:  0.250 free air  Special Features: Terminals spaced 0.150 in. C to c  Style Designator: Axial terminals one end  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
0.250 free air  Special Features: Terminals spaced 0.150 in. C to c  Style Designator: Axial terminals one end  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.312 inches
Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Terminals spaced 0.150 in. C to c  Style Designator:  Axial terminals one end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.250 free air
Style Designator:  Axial terminals one end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Special Features:
Axial terminals one end  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminals spaced 0.150 in. C to c
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminals one end
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	<u></u>
Fiig:	Demilitarization:
	No
	Fiig:
Autrau	A001a0