NSN 5905-00-778-7886

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-778-7886
Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.7500 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
1.875 inches
Undercut Width:
0.0620 inches
Body Diameter:
2.000 inches
Angle Of Mounting Hole In Deg:
90.0
Angle Between Centerlines Of Mounting Holes In Deg:
120.0
Shaft Diameter:
Between 0.2494 inches and 0.2497 inches
Shaft Length:
0.625 inches
Body Length:
0.969 inches
Mounting Lip Diameter:
1.8750 inches
Mounting Lip Depth:
0.0620 inches
Mounting Hole/stud Circle Diameter:
1.250 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
356.0

Maximum Starting Torque:

1.90 inch-ounces

NSN 5905-00-778-7886



Precision Wire Wound Variable Resistor - Page 2 of 3	Hore
Maximum Running Torque:	
1.20 inch-ounces	
Shaft End Play:	
0.00500 inches	
Shaft Runout:	
0.001 inches	
Lateral Runout:	
0.006 inches	
Pilot Diameter Runout:	
0.00150 inches	
Shaft Radial Play:	
0.002 inches	
Screw Thread Diameter:	
0.164 inches	
Screw Thread Series Designator:	
Unc	
Screw Thready Qty Per Inch (tpi):	
32.0	
Mounting Facility Quantity:	
3	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Threaded hole	
Electrical Resistance Per Section:	
1.667 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-0.50/+0.50 single section	
Power Dissipation Rating Per Section In Watts:	

2.8 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

NSN 5905-00-778-7886

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0