## NSN 5905-00-778-7887

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-778-7887 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.812 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 2.000 inches **Angle Of Mounting Hole In Deg: Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** 0.625 inches **Body Length: 4.312** inches **Mounting Lip Diameter:** 1.8750 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 

3600.0 **Maximum Starting Torque:** 

2.60 inch-ounces

## NSN 5905-00-778-7887



Nonprecision Wire Wound Variable Resistor - Page 2 of 3
Maximum Running Torque:
1.80 inch-ounces
Shaft End Play:
0.00500 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.006 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
2.500 kilohms all sections
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 all sections
Power Dissipation Rating Per Section In Watts:
4.0 7th secondary pattern
Function Conformity Per Section:

All sections independent linearity

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 all sections

**Actuator Travel Control Feature:** 

Clutch

**Function Characteristic Per Section:** 

All sections linear

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 all sections

## NSN 5905-00-778-7887

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Termi	nal Type And	Quantity:
6 tab,	solder lug	

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0