NSN 5905-00-779-1506

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-779-1506

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0 Electrical Resistance: 260.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A001a0	
Electrical Resistance: 260.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
260.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-20.0/+20.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	260.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-55.0/+145.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Terminal Length: 0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
0.500 inches Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Length:
0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.500 inches
Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
0.312 inches Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Power Dissipation Rating In Watts: 0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
0.250 free air Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.312 inches
Special Features: Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Terminals spaced 0.150 in. C to c Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Style Designator: Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Axial terminals one end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminals spaced 0.150 in. C to c
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminals one end
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	<u></u>
Fiig:	Demilitarization:
	No
	Fiig: