## NSN 5905-00-779-5267

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-779-5267 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.7495 inches and 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 2.431 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.0570 inches **Body Diameter:** Between 0.870 inches and 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** Between 0.469 inches and 0.531 inches **Body Length:** 1.900 inches **Overall Diameter:** 1.455 inches **Mounting Lip Diameter:** Between 0.8700 inches and 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.90 inch-ounces **Maximum Running Torque:** 

0.80 inch-ounces

**Shaft End Play:** 

0.00500 inches

## NSN 5905-00-779-5267

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.000 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-3.50/+3.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-600.0/+600.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
6 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-00-779-5267

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0