## NSN 5905-00-779-8303

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-779-8303

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -20.0/+20.0   |
| Electrical Resistance:  |
| 50.000 kilohms  |
| Resistance Tolerance In Percent:  |
| -0.250/+0.250   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 125.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 145.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0/+145.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 0.500 inches  |
| Body Diameter:  |
| 0.250 inches  |
| Body Length:  |
| 0.312 inches  |
| Power Dissipation Rating In Watts:  |
| 0.250 free air  |
| Special Features:   |
| Terminals spaced 0.150 in. C to c   |
| Style Designator:   |
| Axial terminals one end   |
| Test Data Document:   |
| 88818-c600007467 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                     |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| ۸001a0  |