Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-779-8374

······································	
Section Quantity:	
1	
Body Style:	
Rectangular	
Reliability Indicator:	
Not established	
Overall Length:	
Between 0.515 inches and 0.555 inches	
Terminal Length:	
0.172 inches	
Overall Height:	
Between 0.490 inches and 0.510 inches	
Overall Width:	
0.372 inches	
Shaft Diameter:	
0.078 inches	
Shaft Length:	
Between 0.025 inches and 0.045 inches	
Body Length:	
0.500 inches	
Body Width:	
0.235 inches	
Body Height:	
0.500 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
Between 7200.0 and 16200.0	
Center To Center Distance Between Terminals:	
0.200 inches	
Fragility Factor:	
Moderately delicate	
Terminal Location:	
Left adjacent side two rows	
Mounting Method:	
Terminal	
Center To Center Distance Between Terminal Rows:	
0.100 inches	
Electrical Resistance Per Section:	
50.0 kilohms single section	

NSN 5905-00-779-8374 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-600.0 to 600.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-22097/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A002a0