## NSN 5905-00-780-8548

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-780-8548

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.080 inches
Shaft Length:
0.040 inches
Body Length:
0.500 inches
Body Width:
0.187 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
15120.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
15120.0
Ambient Tempurature In Dea Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## NSN 5905-00-780-8548

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.5 7th secondary quality

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

**Demilitarization:** 

No

Fiig:

A002a0