NSN 5905-00-780-8736

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-780-8736

Section Quantity:
1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Overall Length:
Between 2.610 inches and 2.766 inches
Shaft Diameter:
Between 0.248 inches and 0.250 inches
Shaft Length:
Between 0.907 inches and 0.969 inches
Mounting Bushing Length:
Between 0.344 inches and 0.406 inches
Body Length:
Between 1.531 inches and 1.593 inches
Body Width:
Between 0.859 inches and 0.891 inches
Body Height:
Between 0.984 inches and 1.016 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3590.0 and 3610.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Maximum Stop Torque:
50.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
Between 0.422 inches and 0.454 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0

32.0

NSN 5905-00-780-8736

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
2.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 3590.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0