

View Online at <https://aerobasegroup.com/nsn/5905-00-780-9751>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.6240 inches and 0.6250 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Overall Length:

2.225 inches

Undercut Diameter:

0.625 inches

Undercut Width:

Between 0.0570 inches and 0.0670 inches

Body Diameter:

Between 0.870 inches and 0.880 inches

Shaft Diameter:

0.124 inches

Shaft Length:

Between 0.620 inches and 0.630 inches

Body Length:

1.600 inches

Overall Diameter:

1.062 inches

Mounting Lip Diameter:

Between 0.8700 inches and 0.8800 inches

Mounting Lip Depth:

Between 0.0580 inches and 0.0680 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Shaft End Play:

0.00400 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.00150 inches

Shaft Radial Play:

0.002 inches

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Flange

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

2.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.15/+0.15 single section

Power Dissipation Rating Per Section In Watts:

0.3 free air single section

Function Conformity Per Section:

Single section absolute linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

105.0 single section

Test Data Document:

05257-x903008 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0