NSN 5905-00-781-3147

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-781-3147 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.285 inches and 0.315 inches **Shaft Diameter:** 0.090 inches **Shaft Length:** 0.040 inches **Body Length:** Between 0.360 inches and 0.390 inches **Body Width:** Between 0.188 inches and 0.218 inches **Body Height:** Between 0.360 inches and 0.390 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

0.100 inches

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

NSN 5905-00-781-3147

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
95542-138-192 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No.