Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-781-3341

# Section Quantity:

1

Body Style:

Cylindrical

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.785 inches

#### **Body Length:**

0.422 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### **Terminal Location:**

Rear end

# Mounting Method:

Tab

### Features Provided:

Grounded contact arm

### **Electrical Resistance Per Section:**

500.000 ohms single section

### Rotary Actuator Travel In Angular Deg:

240.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

## Power Dissipation Rating Per Section In Watts:

1.25 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

## Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0