NSN 5905-00-781-3773

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-781-3773

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|---|
| -400.0/+400.0 |
| Electrical Resistance: |
| 1.500 ohms |
| Resistance Tolerance In Percent: |
| -5.000/+5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 350.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+350.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 0.188 inches |
| Body Length: |
| 0.500 inches |
| Power Dissipation Rating In Watts: |
| 3.000 free air |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Departure From Cited Designator: |
| As mod by delete 0.00175 in para.3.2.1.1 and sub. 0.001; delete para. 3.5 and sub. The temp coef or res shall not exceed porm 0.0025 pct |
| /25ppm/ per degrees c thermal emf of the res wire versus copper shall not exceed 10 microvolts per degrees c; para 3.15 res may be |
| marked and labelled according to commercial practice |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |