

View Online at <https://aerobasegroup.com/nsn/5905-00-781-7218>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.8750 inches

Pilot Length:

0.0620 inches

Overall Length:

1.970 inches

Undercut Diameter:

1.984 inches

Undercut Width:

0.0730 inches

Body Diameter:

2.000 inches

Angle Of Mounting Hole In Deg:

45.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

0.250 inches

Shaft Length:

0.250 inches

Body Length:

1.412 inches

Overall Diameter:

1.500 inches

Mounting Lip Diameter:

2.01625 inches

Mounting Lip Depth:

0.0930 inches

Mounting Hole/stud Circle Diameter:

1.875 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

50.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

3 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0