NSN 5905-00-781-7274

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-781-7274 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.6240 inches and 0.6250 inches Pilot Length: Between 0.0600 inches and 0.0640 inches **Overall Length:** Between 3.568 inches and 3.666 inches **Undercut Diameter:** Between 0.6240 inches and 0.6250 inches **Undercut Width:** Between 0.0630 inches and 0.0740 inches **Body Diameter:** Between 0.865 inches and 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Body Length:** Between 3.099 inches and 3.135 inches **Overall Diameter:** Between 1.037 inches and 1.047 inches **Mounting Lip Diameter:** 0.8700 inches **Mounting Lip Depth:** Between 0.0580 inches and 0.0630 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.70 inch-ounces

__ . _ _ . _

Maximum Running Torque:

0.50 inch-ounces

NSN 5905-00-781-7274

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
0.70 inch-ounces
Shaft End Play:
0.00200 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.000 kilohms all sections
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 all sections
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Maggura:

-

NSN 5905-00-781-7274

Precision Wire Wound Variable Resistor - Page 3 of 3



em			

No

Fiig:

A002a0