NSN 5905-00-781-8803

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-781-8803

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.412 inches
Terminal Length:
Between 0.177 inches and 0.197 inches
Body Diameter:
Between 0.490 inches and 0.510 inches
Body Length:
Between 0.215 inches and 0.235 inches
Overall Diameter:
Between 0.490 inches and 0.510 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:

A single section

NSN 5905-00-781-8803

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screwdriver slot provided for adjustment

Test Data Document:

18876-10125246 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0