## NSN 5905-00-782-0890

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-782-0890 **Section Quantity:** 2 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.062 inches **Body Length:** 1.250 inches **Body Width:** 0.500 inches **Body Height:** 0.313 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 200.000 ohms all sections

**Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 all sections

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 all sections

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air all sections

## NSN 5905-00-782-0890

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percent:                        |
|---|
| -10.0 to 10.0 all sections  |
| Actuator Travel Control Feature:                                    |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 all sections   |
| Standard Taper Curve Per Section:                                   |
| A all sections  |
| Terminal Type And Quantity:   |
| 6 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |