Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-782-7388

#### Section Quantity:

1

**Body Style:** 

Cylindrical servo mounted

#### **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

0.7500 inches

#### **Pilot Length:**

0.0620 inches

#### **Overall Length:**

1.000 inches

#### Undercut Diameter:

0.781 inches

#### **Undercut Width:**

#### 0.0620 inches

**Body Diameter:** 

0.891 inches

#### Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

0.500 inches

#### **Body Length:**

0.500 inches

#### **Overall Diameter:**

1.070 inches

#### Mounting Lip Diameter:

0.8750 inches

#### Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

348.0

## Maximum Starting Torque:

0.50 inch-ounces

## Maximum Running Torque:

0.50 inch-ounces

# NSN 5905-00-782-7388 Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft Runout:0.001 inchesLateral Runout:0.002 inchesPilot Diameter Runout:0.001 inchesShaft Radial Play:0.001 inchesTerminal Location:Radially positioned over less than half the circumferenceMounting Method:Clamp ringFeatures Provided:Nonmetallic shaft

**Electrical Resistance Per Section:** 

400.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

360.0

**Function Conformity Tolerance Per Section:** 

-0.50/+0.50 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-500.0/+500.0 single section

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

#### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

**Function Characteristic Per Section:** 

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

#### Special Features:

Spring loaded shaft

**Terminal Type And Quantity:** 

3 turret

Shelf Life:

N/a

Unit Of Measure:

# NSN 5905-00-782-7388

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0