NSN 5905-00-782-7744

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-782-7744 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Pilot Diameter:** Between 1.87400 inches and 1.87500 inches Pilot Length: 0.06200 inches **Overall Length:** 4.594 inches **Terminal Length:** 0.188 inches **Undercut Diameter:** Between 1.874 inches and 1.875 inches **Undercut Width:** 0.07300 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.656 inches **Body Length:** 1.779 inches **Mounting Lip Diameter:** 2.00000 inches **Mounting Lip Depth:** 0.062000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 355.0 and 357.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:**

500.000 ohms c and better industrial clears

Rotary Actuator Travel In Angular Deg:

360.0

NSN 5905-00-782-7744

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Tolerance Per Section: -0.23/+0.23 2nd section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -20.0/+20.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 5 2nd section **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 2nd section **Actuator Travel Control Feature:** Continuous motion **Criticality Code Justification:** Zzzy **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 13 turret **Reference Number Differentiating Characteristics:** Selected and tested for special propulsion plant Shelf Life: N/a **Unit Of Measure: Demilitarization:**