NSN 5905-00-782-7848

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-782-7848 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Terminal Length:** Between 0.172 inches and 0.202 inches **Mounting Hole Diameter:** 0.064 inches **Shaft Diameter:** 0.098 inches **Shaft Length:** 0.085 inches **Body Length:** 0.380 inches **Body Width:** 0.195 inches **Body Height:** 0.413 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.190 inches and 0.210 inches **Lateral Distance Between Mounting Hole Centers:**

0.415 inches **Mounting Facility Quantity: Terminal Location:** Right adjacent side single row **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft

NSN 5905-00-782-7848

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:	
1.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
9000.0	
Center To Center Distance Between Center Terminal And Outside Terminal:	
Between 0.095 inches and 0.105 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
150.0 single section	
Power Dissipation Rating Per Section In Watts:	
1.0 free air single section	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
50.0 single section	
Terminal Type And Quantity:	
3 pin	
Specification Data:	
09344-pc5177 manufacturers specification control	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A002a0	