Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-782-7992

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# **Reliability Indicator:**

Not established

## Mounting Hole Diameter:

0.088 inches

### Shaft Diameter:

0.115 inches

- Shaft Length:
- 0.070 inches

Body Length:

1.125 inches

Body Width:

# 0.190 inches

**Body Height:** 

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

792.0

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

**Terminal Location:** 

Rear end

## **Mounting Method:**

Terminal

## **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

2.0 megohms single section

# Rotary Actuator Travel In Angular Deg:

7920.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section



## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### **Actuator Travel Control Feature:**

Clutch

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0