NSN 5905-00-784-2228

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-784-2228

| Section Quantity: |
|--|
| 1 |
| Body Style: |
| Rectangular w/mounting holes/slots |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 1.308 inches |
| Overall Height: |
| 0.446 inches |
| Overall Width: |
| Between 0.235 inches and 0.300 inches |
| Mounting Hole Diameter: |
| Between 0.088 inches and 0.098 inches |
| Shaft Diameter: |
| Between 0.100 inches and 0.140 inches |
| Shaft Length: |
| 0.058 inches |
| Body Length: |
| 1.250 inches |
| Body Width: |
| Between 0.235 inches and 0.300 inches |
| Body Height: |
| Between 0.280 inches and 0.374 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| Between 6120.0 and 9720.0 |
| Lateral Distance Between Mounting Hole Centers: |
| Between 0.995 inches and 1.005 inches |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Lower adjacent side single row |
| Mounting Method: |
| Unthreaded hole |
| Electrical Resistance Per Section: |
| 20.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| Between 6120 0 and 9720 0 |

Between 6120.0 and 9720.0

NSN 5905-00-784-2228

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-600.0 to 600.0 single section

Power Dissipation Rating Per Section In Watts:

0.3 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-22097/1 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0