## NSN 5905-00-784-6100



Nonprecision Nonwire vyound variable Resistor - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5905-00-784-6100
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.328 inches
Body Diameter:
0.500 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.500 inches
Body Length:
0.453 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock and at 9 oclock
Nonturn Device Radius:
0.245 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Locking husbing

**Electrical Resistance Per Section:** 

1.000 kilohms single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

## NSN 5905-00-784-6100

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:	
-10.0 to 10.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0