NSN 5905-00-786-3393

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-786-3393 **Section Quantity: Body Style:** Cylindrical servo mounted **Pilot Diameter:** Between 1.31200 inches and 1.31250 inches Pilot Length: Between 0.05700 inches and 0.05800 inches **Overall Length:** 1.550 inches **Undercut Diameter:** 1.313 inches **Undercut Width:** 0.05700 inches **Body Diameter:** 1.450 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** Between 0.590 inches and 0.650 inches **Body Length:** 0.900 inches **Mounting Lip Diameter:** Between 1.43000 inches and 1.44000 inches **Mounting Lip Depth:** Between 0.08800 inches and 0.09800 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 311.92 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:**

Clamp ring

Electrical Resistance Per Section:

3.500 kilohms single section

Function Conformity Tolerance Per Section:

-0.40/+0.40 single section

NSN 5905-00-786-3393

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2

